

SPECIFICATIONS

STICK DMX Control Panel w/ Software



PRODUCT NAME	STICK DMX Control Panel w/ Software
URL	Click Here
SKU	LC-NL-DMX-STICK
DESCRIPTION	This DMX controller features a touch-sensitive wall-mounted faceplate for easy control of two separate DMX 512 channel universes. This DMX controller can be controlled live via a USB connection and included software (ESA Pro) or DMX programs can be written to an included mini-SD card to run in stand alone mode. A built in microphone allows for sound activation of a user-built DMX scene. Two programs are included for setting up your DMX lighting control, both Sunlite Easy Stand Alone and ESA Pro softwares. S.T.I.C.K hardware faceplate, software CD-ROM, user manual, mini USB cable, mini SD card with adapter, and 9VDC power supply included. Software is compatible with Windows XP, Vista, and Windows 7 (32 and 64-bit versions). The optional COM+ package provides an Ethernet card allowing for IP addressing of a S.T.I.C.K. controller. The COM+ package also allows for the ability to be controlled via a smart phone application through the use of a networked Wi-Fi connection. Additional items included with a COM+ package are infrared remote control, RS232 three pin capability (RX TX and GND), four additional ports (5-8), two wire audio input and two wire relay.
DIMENSIONS	9.8" H X 5.9" W X 2.2" T (250 X 150 X 55mm)
DMX UNIVERSES	2 DMX 512
SCENES	200
ZONES	5
PORT/CLOCK TRIGGERING	8/40
SUPPLY VOLTAGE	9V DC via wall plug power pack or USB cord connection
RATING	Indoor / Dry
CONNECTION TYPE	1 USB port, 8-pin I/O port, SD Card w/ adapter, RS232, Audio-In, Ethernet
WARRANTY	1 Year Manufacturers

These specification are subject to change without notice. This specification information is from the manufacturer of this product. Eco Light LED is not the manufacturer of this product.
Copyright © 2010 Eco Light LED

ECOLightLED.com
info@ECOLightLED.com

ECO LIGHT
LED Lighting Solutions

775-636-6060
866-348-3492